

Serie CONCRETE JUNGLE - SPECIFICATION ITEMS

1. Natural porcelain stoneware tiles, unglazed (Bla-UGL group), compact and non-absorbent, aesthetically similar to natural stone, suitable for prestigious internal and external public, commercial environments subject to heavy pedestrian traffic.
2. Made by dry-pressing fine, coloured, spray died bodies with the appropriate grain size, subject to prolonged industrial firing at a temperature of at least 1200° C

	CONCRETE JUNGLE	CONCRETE JUNGLE HONED
Degree of shading ANSI A137.1	V2 Low	V2 Low
Riflectivity	Satin	Opalescent
Surface	Slightly rough	Soft
Surface texture	Spatulated	Spatulated
Sides	Rectified	Rectified
Edges	Regular	Regular
Corners	Sharp	Sharp

3. Complying with European standard EN 14411-G and International standard ISO 13006-G.
4. Manufactured in facilities with **ISO 9001 Quality Management System**.
5. Manufactured with the greatest attention towards the environment in facilities certified by the **ISO 14001 Environmental Management and EMAS system**.
6. Tiles with top quality technical features that make them particularly suitable for the uses indicated in point 1:

	CONCRETE JUNGLE	CONCRETE JUNGLE HONED
Technical characteristics	Production average values for available versions	
Reference standard		
Water absorption	≤ 0,1	≤ 0,1
ISO 10545-3		
Bending strength	≥ 50 N/cm ²	≥ 50 N/cm ²
ISO 10545-4	≥ 510 Kg/cm ²	≥ 510 Kg/cm ²
Breaking strength (S)	Conformity	Conformity
ISO 10545-4		
Deep abrasion resistance	≤ 145 mm ³	≤ 145 mm ³
ISO 10545-6		
Frost resistance	Frost proost	Frost proost
ISO 10545-12		
Resistance to chemical etching	ULA - UHA	ULA - UHA
ISO 10545-13		
Stain resistance	CLASSE 5	CLASSE 5
ISO 10545-14		
Slip resistance		
DIN 51130	R10	R9
DIN 51097	A+B	-
BCRA		
TORTUS	> 0,40	> 0,40
ANSI A137.1 - BOT3000 DCOF	≥ 0,42	≥ 0,42